




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04Q 7/38, 7/32	A1	(11) International Publication Number: WO 98/59513 (43) International Publication Date: 30 December 1998 (30.12.98)
(21) International Application Number: PCT/FI98/00469 (22) International Filing Date: 2 June 1998 (02.06.98) (30) Priority Data: 972722 24 June 1997 (24.06.97) FI (71) Applicant (for all designated States except US): NOKIA MOBILE PHONES LTD. [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI). (72) Inventor; and (75) Inventor/Applicant (for US only): LINTULAMPI, Raino [FI/FI]; Teponkentäntie 9, FIN-90810 Kiviniemi (FI). (74) Agent: JOHANSSON, Folke; Nokia Mobile Phones Ltd., P.O. Box 100, FIN-00045 Nokia Group (FI).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: METHOD OF OPERATING A DUAL MODE MOBILE TELEPHONE**(57) Abstract**

A method of operating a mobile telephone within a geographical area having overlapping coverage from a first, GSM, network and a second, UMTS, network, where said GSM network is the home network (HPLMN) of the mobile communication device and said GSM and UMTS networks provide respective first and second sets of services in said geographical area. The method comprises registering the telephone with the GSM network when a service of said first set is requested and registering the device with the UMTS network when a service of said second set, but not of said first set, is requested. The method provides the mobile telephone with a roaming for service function.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

METHOD OF OPERATING A DUAL MODE MOBILE TELEPHONE

The present invention relates to mobile communication systems and more particularly to a method of operating a mobile communication device within a geographical area having
5 overlapping coverage from first and second mobile telephone networks, where said first network is the home network of the mobile communication device and said first and second networks provide respective first and second sets of services. The present invention also relates to a system for performing this method of operation.

10 A number of digital mobile telephone standards are in use throughout the world. These include the European GSM standard and the US TDMA standard. However, due to the ever increasing demand for mobile telephone services many, if not all of these standards are likely to be superseded by new standards offering increased network capacity and/or increased data transmission rates. In particular, the European Telecommunications
15 Standards Institute (ETSI) is currently developing a so called third generation mobile environment known as the Universal Mobile Telecommunication System (UMTS) which it is expected will be operational by 2002. UMTS will operate in the 2GHz frequency band and will offer data transmission rates of up to 2Mbits/sec, compared to a rate of only 9.6Kbits/sec offered by the existing GSM standard.

20 In the transition from second generation standards to third generation standards, there is likely to be a period when both second and third generation standards will have to coexist. It is also possible that such coexisting networks will be operated by different operators. As with all previous standards, networks implementing the new standards are likely to be
25 introduced piece-meal, extending their geographical coverage over time. It may also be the case that the geographical coverage offered by third generation networks will always be less than that offered by second generation networks due to the need to sustain high bit rate transmissions with the former.

30 It is proposed (in Europe at least) to enable mobile stations registered with a third generation network as the "home" network (i.e. the network to which the mobile stations subscribe) to transfer to a second generation network when the stations are outside the coverage area of the home network, with appropriate cross-billing agreements between the network operators, to alleviate the possible geographical limitations. This transfer will operate in substantially
35 the same way as the "roaming" function of conventional GSM networks (GSM 03.22) where a station can register with an alternative network when the RF connection between the

mobile station and the home network is too weak to support a traffic channel. Of course third generation terminals will have to be dual mode, e.g. UMTS/GSM, in order to take advantage of this facility.

- 5 The inventors of the present invention have addressed the problem of how mobile stations registered with earlier generation networks, e.g. second generation networks, as their home network may gain access to new services only available through new generation networks, e.g. third generation networks. This may be a requirement of reciprocal arrangements between second and third generation network operators. As far as the inventors are aware
10 this problem has not been previously addressed.

According to the present invention there is provided a method of operating a mobile communication device within a geographical area having overlapping coverage from first and second mobile telephone networks, where said first network is the home network of the
15 mobile communication device and said first and second networks provide respective first and second sets of services in said geographical area, the method comprising registering the device with said first network when a service of said first set is requested and registering the device with said second network when a service of said second set, but not of said first set, is requested.

20 Typically, although not essentially, the overall geographical coverage of said second network is less than that of said first network, as is likely to be the case in the period following the introduction of a new mobile telephone standard which is implemented by said second network.

25 Preferably, a service provided by said second network, but not by said first network, is a high transmission rate service, that is at a higher transmission rate than is possible with services provided by said first network. Examples of high bit rate services are internet browsing, videophone, and data downloading.

30 The request for a service may be made by the mobile communication device, e.g. in response to a user input, or by the first network, e.g. in response to an incoming call made to the mobile communication device. In either case, in the event that a service of said second set, but not of said first set, is requested, registration with said second network may be
35 carried out automatically under the control of said first network. In this event, there is no need for the user of the mobile communication device to be aware of the change of

registration. Alternatively, a decision on a change of registration may be made by a user via a user interface of the mobile communication device.

5 In one embodiment of the present invention, said first network is a GSM network and said second network is a UMTS network and said mobile communication device is a dual mode UMTS/GSM device.

10 According to a second aspect of the present invention there is provided a mobile telecommunication system comprising at least first and second mobile telephone networks having an overlapping geographical area of coverage and a multiplicity of mobile communication devices, wherein said first network is the home network of the mobile communication devices and said first and second networks are arranged to provide respective first and second sets of telephonic services in said geographical area, the system comprising control means for registering a communication device with said first network
15 when a service of said first set is requested and for registering the device with said second network when a service of said second set, but not of said first set, is requested.

The control means may comprise means associated with each of the mobile communication devices for transmitting a deregistration request to the first network and for transmitting a
20 registration request to the second network when a service of said second set, but not of said first set, is requested. Alternatively, the control means may comprise means associated with the first network for responding to a request from a communication device for a service of said second set, but not of said first set, by re-registering the communication device with the second network.

25 The mobile communication devices may be, for example, mobile telephones, combined mobile telephone/personal digital assistant devices, or other devices which use wireless telephonic communication.

30 For a better understanding of the present invention and in order to show how the same may be carried into effect reference will now be made, by way of example, to the accompanying drawings, in which:

Figure 1 shows schematically the geographical coverage area of example second and third
35 generation mobile telephone networks;

Figure 2 shows in block diagram form the architectures of the second and third generation networks of Figure 1;

Figure 3 shows a flow diagram of the operation of a mobile station in the coverage area of the networks of Figure 1;

- 5 Figure 4 shows at the signaling level an implementation of the method of Figure 3 for circuit switched transmission; and

Figure 5 shows at the signaling level an implementation of the method of Figure 3 for packet switched transmission.

- 10 As already noted above, in Europe, UMTS networks are likely to be introduced with only limited geographical coverage. This situation is illustrated in Figure 1 where the coverage 1 provided by the UMTS network falls within the coverage area 2 of a pre-existing GSM network. When a UMTS compatible mobile station (MS) 3, which has the UMTS network as its home network (or home public land mobile network HPLMN), is located within the UMTS
- 15 network coverage area 1, the MS 3 is registered with the UMTS network and is able to make use of all the services provided by that network (or at least those services to which the MS user has subscribed). Providing that the MS is also GSM compatible, and that an appropriate agreement exists between the operators of the UMTS and GSM networks, when the MS detects that it has moved outside of the UMTS network coverage area 1 it is able to
- 20 register with the GSM network (as a visiting public land mobile network VPLMN) and to make use of the services provided by the GSM network. The services provided by the GSM network are likely to be more limited than those provided by the UMTS network but this disadvantage is more than offset by the increased coverage area available to the UMTS network subscriber. This arrangement is similar in principle to the 'roaming for coverage'
- 25 function available with current GSM MSs, e.g. which operates when a MS moves from one country to another, as defined in GSM specification 03.22.

The architectures of the GSM and UMTS networks are shown schematically in Figure 2 where the dual-mode GSM/UMTS MS 3 communicates with either the UMTS BSS (base

30 station subsystem) 4 and the GSM/GPRS (global packet radio service) core network 5 or with the GSM/DCS BSS 6 and the GSM/GPRS core network 7. The two core networks 5,7 cooperate according to a roaming agreement between the two network operators.

- Consider now the case where the MS 3 is registered with the GSM network as its HPLMN.
- 35 The MS 3 may make use of the GSM services throughout the GSM coverage area 2, including the UMTS coverage area 1 because of the overlapping coverage which exists

there. However, if the MS 3 requires to make use of a service provided by a UMTS network (i.e. as a VPLMN) but not by the GSM network, the MS 3 must 'roam' for that service. This is different from the conventional 'roaming for coverage' offered by GSM and is not defined in GSM specification 03.22. Figure 3 is a flow diagram of the roaming for service operation
 5 illustrating that the HPLMN will be selected by the MS 3 so long as that network is available and the selected service is provided by the HPLMN.

Roaming for service differs from traditional roaming for coverage in that, with the former, location updates and thus location registration are not necessarily required because the MS
 10 3 can remain registered with the home GSM network which knows the location of the MS 3.

Figure 4 illustrates a possible implementation scenario for the roaming for service function where data transmission between the MS 3 and the networks is by circuit switched transmission (i.e. where one or more traffic channels are reserved for the duration of the
 15 transmission). The following legends are used in Figure 4:

MS	Mobile Station
RAN	Radio Access Network
CN	Core Network
GSM-op	GSM operator, owner of the first network
20 UMTS-op	UMTS operator, owner of the second network

The following table contains a description of the messages of Figure 4:

A-HORequired	indication from the radio access network that handover is needed
MAP-prepare-HO	handover request between networks
A-HORequest	handover request to the radio access network
A-HOAck	acceptance of handover request from the radio access network
MAP-prepare-HO-resp	response to handover request between networks
A-HOCommand	handover command to the radio access network
HOCommand	handover command to the MS
HOAccess	MS sends access attempt to the radio access network
A-HOdetect	the radio access network informs network that the MS's access attempt has been detected
MAP-process-access-sig	indication that handover process is ongoing
HOComplete	the radio access network informs the MS that handover process has been completed
A-HOComplete	the radio access network informs network that handover process has been completed

MAP-send-end-sig	the second network informs the first network that handover process has been completed
A-clr-command	the first network commands the radio access network to release reserved radio resources

Signaling can be divided into eight main steps as follows:

1. The MS sends a service request with quality of service (QoS) parameters to the GSM network. These QoS parameters may include bit transmission rate, bit error rate, and transmission delay.
2. The GSM network analyses the available resources for the service. The GSM network detects that it cannot provide the requested quality of service thus it sends a handover request to the UMTS network.
3. The UMTS network accepts the handover request. The MS is commanded to the UMTS network with handover command and the MS makes an access attempt after the MS has changed to the UMTS network's cell.
4. Handover access has been detected by the UMTS network and the resources of the GSM network are released.
5. The MS continues the service request signaling with the UMTS network.
6. The UMTS network starts billing procedure in order to bill the GSM network for the service.
7. When the service is released the billing procedure is stopped.
8. The MS selects the GSM network if it is available.

Figure 5 illustrates a possible implementation scenario for the roaming for service function where data transmission between the MS 3 and the networks is by packet switched transmission (i.e. where transmission time slots are dynamically allocated for transmission according to demand and priority). The following legends are used in Figure 5:

MS	Mobile Station
BSS	Base Station Subsystem
SGSN	Service GPRS Support Node
GPRS	General Packet Radio Service
GGSN	Gateway GPRS Support Node
RAN	Radio Access Network
IP	Destination Internet Protocol Node

The following table contains a description of the messages of Figure 5:

SENDER(session, sender_Tspec)	application session in the MS requests quality of service described in sender_Tspec
UPCALL(session, resv_error)	error message with code "quality of service cannot be provided"
MM-RA-update	routing area update message
SGSN context request	context for the MS is requested
GTP-SGSN context request	context request between two GGSNs
GTP-SGSN context response	context request confirmation
Cancel location	location canceled from the previous SGSN
Cancel location ack	location cancellation acknowledgment
SGSN context response	the MS context activation accepted by GGSN
MM-RA- updateAccepted	routing area updating confirmation
path(sender, sender_Tspec)	quality of service request to the destination IP node
rsvp(Tspec)	merged quality of service request to the previous IP node
UPCALL(session, resv_confirm)	connection and quality of service confirmation
RELEASE(session)	session release
resvTear(session)	resource release between IP nodes

Again, signaling can be divided into eight main steps as follows:

- 5 1. Application in the MS sends a service request with quality of service parameter to the GSM network.
2. Available radio resources are analysed and a service request is rejected due to the lack of resources. The MS selects the UMTS network.
3. The GSM and the UMTS network exchange information about the MS and finally the UMTS network accepts the MS to access the network.
- 10 4. Application in the MS sends a service request with quality of service parameter to the UMTS network.
5. The UMTS network has radio resources available and it sends path-message to the destination IP node. Resources for the session are found and the MS is confirmed about the resource reservations.
- 15 6. Data transfer between application starts. Billing and roaming starts.
7. Application is closed or timer expires. The session is closed and resource reservations are released.

8. The MS selects the GSM network. The UMTS network bills the GSM network for the service.

5 In the implementations of Figures 4 and 5, it is the GSM network which determines, from the request made by the MS, whether or not it can provide the requested service and therefore whether or not the MS must be handed over to the UMTS network. In this way, the operation can be transparent to the user who is unaware that a handover has occurred. In an alternative approach however, the MS may be configured such that it is able to determine when a requested service is not provided by the GSM network. The MS may then
10 automatically, or following a prompt from the user, de-register with the GSM network and subsequently register with the UMTS network.

It will be appreciated by those of skill in the art that further modifications may be made to the above described embodiments without departing from the scope of the present invention.
15 For example, the invention may be used to provide service roaming between any two or more networks which provide different numbers or levels of service, e.g. two GSM or two UMTS networks.

Glossary

	BSS	Base Station Subsystem
	DCS	Digital Cellular System (at 1800 MHz)
	DECT	Digital European Cordless Telecommunications
5	HLR	Home Location Register
	HPLMN	Home Public Land Mobile Network
	IETF	Internet Engineering Task Force
	IMSI	International Mobile Subscriber Identity
	IP	Internet Protocol
10	GPRS	General Packet Radio Service
	GSM	Global System for Mobile Communications
	MS	Mobile Station
	RSVP	Reservation Set-up Protocol
	UMTS	Universal Mobile Telecommunications System

Claims



1. A method of operating a mobile communication device within a geographical area
5 having overlapping coverage from first and second mobile telephone networks, where said first network is the home network of the mobile communication device and said first and second networks provide respective first and second sets of services in said geographical area, the method comprising registering the device with said first network when a service of said first set is requested and registering the device with said second network when a
10 service of said second set, but not of said first set, is requested.
2. A method according to claim 2, wherein the overall geographical coverage of said second network is less than that of said first network.
- 15 3. A method according to claim 1 or 2, wherein a service provided by said second network, but not by said first network, is a high transmission rate service.
4. A method according to any one of the preceding claims, wherein the request for a service is made by the mobile communication device in response to a user input.
20
5. A method according to any one of claims 1 to 3, wherein the request for a service is made by the first network in response to an incoming call made to the mobile communication device.
- 25 6. A method according to claim 4 or 5, wherein, in the event that a service of said second set, but not of said first set, is requested, registration with said second network is carried out automatically under the control of said first network.
7. A method according to any one of the preceding claims, wherein said first network is
30 a GSM network and said second network is a UMTS network and said mobile communication device is a dual mode UMTS/GSM device.
8. A mobile telecommunication system comprising at least first and second mobile telephone networks having an overlapping geographical area of coverage and a multiplicity
35 of mobile communication devices (3), wherein said first network is the home network of the mobile communication devices (3) and said first and second networks are arranged to

provide respective first and second sets of telephonic services in said geographical area, the system comprising control means (5) for registering a communication device (3) with said first network when a service of said first set is requested and for registering the device (3) with said second network when a service of said second set, but not of said first set, is requested.


9. A system according to claim 8, wherein the control means may comprise means associated with each of the mobile communication devices (3) for transmitting a deregistration request to the first network and for transmitting a registration request to the second network when a service of said second set, but not of said first set, is requested.

10. A system according to claim 8, wherein the control means comprises means associated with the first network for responding to a request from a communication device (3) for a service of said second set, but not of said first set, by re-registering the communication device (3) with the second network.

1/4

Figure 1Figure 2

2/4

Figure 3

3/4




Figure 4

4/4




Figure 5

INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 98/00469

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: H04Q 7/38, H04Q 7/32

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPODOC, WPI

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 9638992 A1 (TELEFONAKTIEBOLAGET LM ERICSSON), 5 December 1996 (05.12.96), page 9, line 27 - page 12, line 32 --	1,2,4,6,8-10
X	WO 9628947 A1 (NOKIA MOBILE PHONES LTD.), 19 Sept 1996 (19.09.96), page 8, line 33 - page 9, line 34; page 11, line 4 - line 6; page 11, line 16 - line 20, page 16, line 11 - line 19; page 17, line 15 - line 29 --	1-6,8-10
A	GB 2289191 A (MOTOROLA INC), 8 November 1995 (08.11.95), see the whole document --	1,8

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

25 November 1998

Date of mailing of the international search report

04.12.98

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Peter Hedman
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 98/00469

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	<p>Fourth International Conference on Intelligence in Services and Networks, IS&N'97 Cernobbio, Italy, May 1997 Proceedings Towards Global Multimedia Mobility (J. C. FRANCIS ET AL) see page 371, line 11 - line 19; page 374, line 1 - page 375, line 12</p> <p style="text-align: center;">-- -----</p>	1-3,7,8

INTERNATIONAL SEARCH REPORT

Information on patent family members

03/11/98

International application No.

PCT/FI 98/00469

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9638992 A1	05/12/96	AU 6019396 A	18/12/96
		EP 0829175 A	18/03/98
		SE 504866 C	20/05/97
		SE 9502003 A	02/12/96

WO 9628947 A1	19/09/96	AU 4881196 A	02/10/96
		EP 0815701 A	07/01/98
		FI 951181 A	14/09/96

GB 2289191 A	08/11/95	GB 2322051 A	12/08/98
		GB 9408381 D	00/00/00
		GB 9809393 D	00/00/00
